

PS10-USSOUND

ELECTRONIC MODULE (Emergency Vehicles: Latin America)



Main Specifications and performances

NOMINAL VOLTAGE	12 / 24 Vdc
VOLTAGE RANGE	10-16 / 20-32 Vdc
CURRENT CONSUMPTION	3,5 / 1,75 A
POWER DRAWN	42 W
FREQUENCY 'L'	430 Hz
FREQUENCY 'H'	570 Hz
SOUND OPTION	Wail, Yelp
OPERATING TEMPERATURE	-40° to +95° °C
STORAGE TEMPERATURE	-40° to +95° °C
CORROSION RESISTANCE	>480 (salt spray test) Hours
OPERATING RELATIVE HUMIDITY	30 to 100 %
CONTINUOUS BLOWING	120 min
VIBRATION (30 min, 3 axis)	1 g
WEIGHT	335 gr
MAIN MATERIALS	Flame Retardant PBT Resin
MAIN APPLICATIONS	Motorbikes, Cars, Trucks, Boats

Conformity to Standards of

PRODUCT	REG.10 ECE
MANUFACTURING	IATF 16949 ISO 9001 ISO 14001 ISO 45001

Other Specifications

MECHANICAL CONNECTION: fix the module to a flat and rigid surface;


HORN'S PROTECTION: the module is IP67, can be mounted inside the engine compartment or inside the passengers compartment;

PACKAGING: color box 125 x 62 x h125 mm;

MASTER CARTON: 8 pieces;

Available Electrical Connection

MOLEX Connector



Dimensions (mm)

